

Steel Flexible Conduits

金屬軟管



Black LSZH Oversheathed Galvanized Steel Flexible Conduit

包膠低烟無毒防水軟管

Size(mm) 尺寸(毫米)	Ø 16	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50
Model No. 產品型號	FCZ16	FCZ20	FCZ25	FCZ32	FCZ40	FCZ50
Nominal Inside Diameter(mm) 標稱內勁(毫米)	16	19	25	31.4	37.2	48.2
Nominal Outside Diameter(mm) 標稱外勁(毫米)	20.3	24.2	31.2	38.4	44.2	54.3
Min.Bending Radius(mm) 最小彎曲半徑(毫米)	45	55	70	110	80	90
Package 包裝	30 m/roll 米/扎	30 m/roll 米/扎	30 m/roll 米/扎	30 m/roll 米/扎	15 m/roll 米/扎	15 m/roll 米/扎

Steel Flexible Conduits

金屬軟管

Relevant Standards

- * IEC 61386-1 (general requirements)
- * IEC 61386-23 (particular requirements)
- * IEC 60529 (IP test)
- * IEC 60695-11-2 (fire hazard test)
- * IEC 60754-1 or 2 (halogen content test)
- * IEC 61034-2 (low smoke emission test)

Product Description

Flexible conduit coupled with adaptors provides high mechanical protection for flexible conduit system and can be widely used in wiring cable installation in railway projects, hospital, schools, government projects and other infrastructure projects applications.

Construction

- * Square locked type made by helically coiling a formed galvanized steel strip sheathed with black LSZH
- * Highly flexible but strong mechanical protection
- * Ingress Protection: IP67

Operating Temperature

-15°C to 90°C

Colour

Black

相關標準

- * IEC 61386-1 (通用要求)
- * IEC 61386-23 (特別要求)
- * IEC 60529 (防塵防水保護檢測)
- * IEC 60695-11-2 (阻燃性檢測)
- * IEC 60754-1 (滷素含量檢測)
- * IEC 61034-2 (低煙檢測)

產品說明

防水軟喉連索咀為軟喉系統提供高機械性保護，適用於鐵路工程項目、醫院、學校、政府工程項目及其他大型基建項目上的安裝。

結構

- * 黑色LSZH膠皮包裹著由鍍鋅銅帶摺成方型緊鎖螺旋形伸展組成
- * 具有高度靈活性和較強的機械保護性
- * 防塵防水級別: IP67

作業溫度

-15°C to 90°C

顏色

黑色