

Steel Flexible Conduits

金屬軟管



Hot Dipped Galvanized Steel Flexible Conduit 熱鍍鋅鋼帶軟管

Size(mm) 尺寸(毫米)	Ø 16	Ø 20	Ø 25	Ø 32
Model No. 產品型號	FCB16	FCB20	FCB25	FCB32
Nominal Inside Diameter(mm) 標稱內勁(毫米)	16	19	25	31.4
Nominal Outside Diameter(mm) 標稱外勁(毫米)	20.2	24.1	31.1	38.3
Min.Bending Radius(mm) 最小彎曲半徑(毫米)	40	50	60	80
Package 包裝	30 m/roll 米/扎	30 m/roll 米/扎	30 m/roll 米/扎	30 m/roll 米/扎

Steel Flexible Conduits

金屬軟管

Relevant Standards

- * IEC 61386-1 (general requirements)
- * IEC 61386-23 (particular requirements)
- * IEC 60529 (IP test)

Product Description

Flexible conduit coupled with adaptors provides high mechanical protection for flexible conduit system and can be widely used in wiring cable installation in residential, commercial and industrial applications.

Construction

- * Square locked type made by helically coiling a formed hot dipped galvanized steel strip
- * Highly flexible but strong mechanical protection and corrosion resistance
- * Ingress Protection: IP40

Operating Temperature

-5°C to 250°C

Colour

Silver

相關標準

- * IEC 61386-1 (通用要求)
- * IEC 61386-23 (特別要求)
- * IEC 60529 (防塵防水保護檢測)

產品說明

防水軟喉連索咀為軟喉系統提供高機械性保護，適用於住宅、商業及工業線路上安裝。

結構

- * 由鍍鋅銅帶摺成方型緊鎖螺旋形伸展組成
- * 具有高度的靈活性和較強的機械保護及耐腐蝕性
- * 防塵防水級別: IP40

作業溫度

-5°C to 250°C

顏色

銀灰色