

Steel Flexible Conduit Adaptors

軟喉索咀



Nickel Plated Female Adaptor
英式軟喉電鍍銅索咀 (內牙)



Nickel Plated Male Adaptor
英式軟喉電鍍銅索咀 (外牙)

Nickel Plated Adaptor (Femal / Male)

Material: Brass

Standard: IEC 61386-1, IEC 61386-23 and IEC 60529

Protection: Nickel plated

Construction: This adaptor comprises two parts, an outer ferrule and body with internal or external thread which can be used to couple two pieces of conduit together tightly without damaging cables passing through.

Ingress Protection: IP54 coupled with flexible conduit FCV or FCZ series while IP40 couple with FCB

英式軟喉電鍍銅索咀 (內牙/外牙)

材質: 黃銅

標準: IEC 61386-1、IEC 61386-23及IEC60529

保護: 鍍鎳

結構: 這組索咀分為兩部份，一個外圈和一個內牙/外牙的主體，可以使兩組踐管接合而不傷害內部的電纜。

防塵防水級別: IP54 (與FCV產品系列或FCZ產品系列連接)
IP40 (與FCB產品系列連接)

Size (mm) 尺寸 (毫米)	Ø20	Ø25	Ø32	Ø40	Ø50
Model No. 產品型號	NPB20F/ NPB20M	NPB25F/ NPB25M	NPB32F/ NPB32M	NPB40F/ NPB40M	NPB50F/ NPB50M
Qty/Ctn 數量(每箱)	1000	500	300	200	50

Nickel Plated Non-thread Bush 英式無牙電鍍銅包臣

Size (mm) 尺寸 (毫米)	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50
Model No. 產品型號	NPB20B	NPB25B	NPB32B	NPB40B	NPB50B
Qty/Ctn 數量(每箱)	2000	1000	1000	500	200

Material: Brass

Standard: IEC 61386-1, IEC 61386-23 and IEC 60529

Protection: Nickel plated

Construction: This is outer ferrule coupled with body with internal or external thread to form 2- part adaptor.

材質: 黃銅

標準: IEC 61386-1、IEC 61386-23 及 IEC60529

保護: 鍍鎳

結構: 這是一套兩件索咀外圈部份，需配一個內牙或外牙的主體組成一完整軟喉索咀。

