

Steel Flexible Conduit Adaptors

軟喉索咀



Female Brass Adaptor
銅索咀母



Male Brass Adaptor
銅索咀公

Brass Adaptor (Female/Male)

Material: Brass

Standard: IEC 61386-1, IEC 61386-23 and IEC 60529

Construction: Type FBA brass adaptor with internal thread which can be used to couple one piece of flexible conduit with one conduit fitting for cable diversion & termination at a junction box or the like. Type MBA brass adaptor with external thread which can be used to couple one piece of flexible conduit with one conduit fitting for cable diversion & termination at a junction box or the like.

Ingress Protection: IP44 coupled with flexible conduit FCV or FCZ series while IP40 couple with FCB

銅索咀(母/公)

材質: 黃銅

標準: IEC 61386-1、IEC 61386-23及IEC60529

結構: FBA型黃銅軟喉接頭配有之內牙，適合把軟喉和過路箱或類似之電器配件連接。MBA型黃銅軟喉接頭配有之外牙，適合把軟喉和過路箱或類似之電器配件連接。

防塵防水級別: IP44 (與FCV產品系列或FCZ產品系列連接)
IP40 (與FCB產品系列連接)

Size (mm) 尺寸 (毫米)	Ø 16	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50
Model No. 產品型號	FBA16/ MBA16	FBA20/ MBA20	FBA25/ MBA25	FBA32/ MBA32	FBA40/ MBA40	FBA50/ MBA50
Qty/Ctn 數量(每箱)	1000	1000	400	200	160	80