

FT-MDL01 SERIES

LED 明裝筒燈

LED Surface Mounted Downlight

MULTIPLE INSTALLATION SURFACE MOUNTED LED DOWNLIGHT

Pendant and surface mounted are optional Die cast aluminum, good quality, Internal driver: LIFUD and BOKE.



鑄鋁材質外殼配透明玻璃面

圓型或方型外殼可選擇

COB LED 芯片, 無頻閃

- ▶ 輸入電壓: $\pm$ AC220V~240V
- ▶ 色溫 (CCT): 3000K/4000K/6500K
- ▶ 顯色指數(CRI): >85 Ra
- ▶ 發光角度 (Beam Angle): 20°



MDL01 系列 圓型外殼



MDLS01 系列 方型外殼



Model	Power	Luminous Flux	Shell Colour	Shell Type	Size (D x H) mm	
MDL01B-10W	10W	800 LM	Black	Round	110	120
MDL01B-20W	20W	1600 LM	Black		130	152
MDL01W-10W	10W	800 LM	White		110	120
MDL01W-20W	20W	1600 LM	White		130	152
Model	Power	Luminous Flux	Shell Colour	Shell Type	Size (LxWxH) mm	
MDLS01B-10W	10W	800 LM	Black	Square	110 x 110 x 120	
MDLS01B-30W	30W	1600 LM	Black		130 x 130 x 135	
MDLS01W-10W	10W	800 LM	White		110 x 110 x 120	
MDLS01W-30W	30W	1600 LM	White		130 x 130 x 135	

Remark: The information technical specification and photographs contained in this literature is representative of general models correct at the time of going to press. In line with our policy of continuous improvement VELOX reserve the right to make any modification necessary to part or details without prior notice (All information in this publication does not form any contract)