

HND630H

Moulded Case Circuit Breaker h630 3P 50kA 630A LSI

Technical characteristics

Architecture

Type of order	Toggle
Number of poles	3 P
Type of pole	3 P

Functions

Complete device with protection unit	Yes
Trip Unit	LSI
Integrated earth fault protection	No

Configuration

Number of modules	8

Main electrical features

Rated operational voltage Ue	220 / 690 V
Frequency	50/60

Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8 kV
With under voltage release	No

Electric current

Rated current	630 A
Rated ultimate short-circuit breaking capacity Icu under 690V AC IEC 60947-2	20 kA
Thermal protection nob setting xIN	0.4 / 0.5 / 0.63 / 0.8 / 0.9 / 0.95 / 1
Breaking capacity on 1 pole for IT 230V NF 60947-2	51 kA
Breaking capacity on 1 pole for IT 400V NF 60947-2	9 kA
Rated service breaking capacity Ics AC according IEC 60947-2	100 %
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity Icu under 440V AC IEC 60947-2	45 kA

Current correction factors	
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	1
Correction factor of rating current for 4 and 5 devices placed side-by-side	1
Correction factor of rating current for 6 devices placed side-by-side	1

Power	
Total power loss under IN	120 W
Power loss per pole at In	40 W

Tripping	
Tripmode	LSI
Thermal protection trip time	5 / 10 / 11 / 16 / 21 ms
Time of response when opening	10 ms

Electrical specifications	
Magnetic trip delay time	100 to 200 ms

Endurance	
Electric endurance in number of cycles	1000
Number of mechanical operations	4000

Installation, mounting	
DIN rail mounting with optional adaptator	No

Connection	
Connection cross-sect. flexible conductor	35 / 240mm²
Connection cross-sect. rigid cable	35 / 240mm²
Connection	Front connection
Type of connection	Terminal

Settings	
Range of the magnetic adjustment	3500 / 4410 / 5600 / 6300 / 6300 / 6300 / 6300 / 6300 A
Magnetic protection nob setting xIN	2.5 / 5 / 8
Setting type In or Ith	IrTh

Equipment	
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive optional	Yes

Use cases	
Category of use	A

Standards	

Standard text	IEC 60947-2
European directive WEEE	concerned

Safety

Protection index IP	IP4X

Use conditions

Operating temperature	-25...70 °C
Altitude	2000 m
Air humidity protection	for all climates
Storage/transport temperature	-35...70 °C

Identification

meta_keyword	Compact circuit-breaker;Circuit-breaker;Main switch;Switch;Circuit-breaker;MCCB;