

Accessories

Dust cup set

A dust collection attachment to be attached to the tip of the tool and used in conjunction with a vacuum cleaner.

For drilling work

HR2670: Part No. 1914L7-6

HR2670FT: Part No. 1914L8-4



For chiseling work

HR2670: Part No. 1914L9-2

HR2670FT: Part No. 1914M0-7



Dust extraction pad set

Part No. 1914X3-8

Sticking the pad to the wall with the suction power of Vacuum cleaner enables drilling into concrete while collecting dust.



Tool holder set

HR2670FT: Part No. 191F47-2



Drill chuck set

HR2670FT: Part No. 191F46-4



Chuck adapter (SDS-PLUS)

Part No. D-14093



Drill chuck set

Part No. 194041-7



Grease vessel set

Part No. 194683-7  
Hammer bit grease



Combination Hammer

HR2670 / HR2670FT 26 mm (1") 3.0 J Combination Hammer, SDS-PLUS

|                                       | HR2670                                                                                                                                                                                     | HR2670FT                                                                                                                                                                       |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Double Insulation                     | Impacts per minute<br>0-4,500 min <sup>-1</sup>                                                                                                                                            | 0-4,500 min <sup>-1</sup>                                                                                                                                                      |
| Variable Speed                        | No load speed<br>0-1,500 min <sup>-1</sup>                                                                                                                                                 | 0-1,500 min <sup>-1</sup>                                                                                                                                                      |
| Reversing                             | Continuous rating input<br>800 W                                                                                                                                                           | 800 W                                                                                                                                                                          |
| Torque Limiter                        | Capacity<br>Concrete (w/ TCT bit): 26 mm (1")<br>Concrete (w/ Core bit): 68 mm (2-11/16")<br>Concrete (w/ Diamond core bit): 80 mm (3-1/8")<br>Steel: 13 mm (1/2")<br>Wood: 32 mm (1-1/4") | Concrete (w/ TCT bit): 26 mm (1")<br>Concrete (w/ Core bit): 68 mm (2-11/16")<br>Concrete (w/ Diamond core bit): 80 mm (3-1/8")<br>Steel: 13 mm (1/2")<br>Wood: 32 mm (1-1/4") |
| Built-in Job Light<br>(HR2670FT only) | Impact energy<br>3.0 J                                                                                                                                                                     | 3.0 J                                                                                                                                                                          |
| Adapted for SDS-PLUS bits             | Vibration level (EN62841-2-6)<br>Hammer drilling into concrete: 16.1 m/s <sup>2</sup><br>Chiselling: 14.2 m/s <sup>2</sup>                                                                 | Hammer drilling into concrete: 15.7 m/s <sup>2</sup><br>Chiselling: 14.0 m/s <sup>2</sup>                                                                                      |
|                                       | Vibration K factor (EN62841-2-6)<br>Hammer drilling into concrete: 1.5 m/s <sup>2</sup><br>Chiselling: 1.5 m/s <sup>2</sup>                                                                | Hammer drilling into concrete: 1.5 m/s <sup>2</sup><br>Chiselling: 1.5 m/s <sup>2</sup>                                                                                        |
|                                       | Sound pressure level (EN62841-2-6)<br>94 dB(A)                                                                                                                                             | 94 dB(A)                                                                                                                                                                       |
|                                       | Sound power level (EN62841-2-6)<br>102 dB(A)                                                                                                                                               | 102 dB(A)                                                                                                                                                                      |
|                                       | Noise K factor (EN62841-2-6)<br>3 dB(A)                                                                                                                                                    | 3 dB(A)                                                                                                                                                                        |
|                                       | Dimensions (L x W x H)<br>362 x 77 x 207 mm (14-1/4 x 3 x 8-1/8")                                                                                                                          | 390 x 77 x 207 mm (15-3/8 x 3 x 8-1/8")                                                                                                                                        |
|                                       | Net weight<br>2.9 - 3.4 kg (6.4 - 7.5 lbs.)                                                                                                                                                | 3.1 - 3.3 kg (6.8 - 7.3 lbs.)                                                                                                                                                  |

Standard Equipment : HR2670: Side grip, Depth gauge, Dust cup assembly  
HR2670FT: Side grip, Depth gauge, Drill chuck assembly

The weight may differ depending on the attachment(s), including the battery cartridge.  
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



Combination Hammer  
HR2670 / HR2670FT

26 mm (1") Adapted for SDS-PLUS bits



Powerful 800 W motor delivers  
3.0 J of impact energy  
to handle the most demanding applications

photo: HR2670

HR2670

Normal chuck



HR2670FT

Quick change chuck  
with LED job light





# Superior Power and Durability

By redesigning the internal structure and optimizing the motor specifications, we have achieved increased power and durability, ensuring superior performance.

Impact energy

3.0 J

|                                                                                                                                                                   |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Drilling efficiency                                                                                                                                               |     |
| Drilled holes downward into concrete with compressive strength of 40N/mm <sup>2</sup> to a depth of 60mm (2-3/8") at a pressing load of 8kg using a two-flute bit |     |
| HR2670<br>ø16.0mm                                                                                                                                                 | 125 |
| HR2670<br>ø10.5mm                                                                                                                                                 | 105 |
| predecessor model                                                                                                                                                 | 100 |


- Dust cup (Optional accessory)

  - Compact and highly visible dust cup
  - The bellows for drilling and for chiseling can be exchanged with one touch.



Reverse switch using Brush holder unit

The same speed and torque even in the reverse rotation



Variable speed control by trigger

Lock-on button

One-touch sliding chuck

Quick change drill chuck (HR2670FT only)



Three operation modes

Rotation only / Rotation with hammering / Hammering only



LED job light (HR2670FT only)



Adapted for SDS-PLUS bits



Hammer drilling using the rotation with hammering mode

photo: HR2670



Chiselling with the hammering mode

photo: HR2670



Drilling with the rotation mode

photo: HR2670FT with Quick change chuck