Product datasheet

Specifications

Power track, Easy series, 32A, 250V, 0.8m, surface mount, white

A3J3PTSM08_WE

Main

Range	Easy Series
Product or component type	Power track
Main colour tint	White
Colour tint	White
[Ue] rated operational voltage	250 V
[In] rated current	32 A
Network type	AC
Network frequency	50 Hz
Device mounting	Surface

Complementary

Product compatibility	Socket-outlet
fixing mode	By 2 installation fasteners
Length	800 mm
Height	21.4 mm
Width	80 mm
Material	Polycarbonate
Surface finish	Textured
surface treatment	Untreated
Ambient air temperature for storage	-5…60 °C
Integrated connection type	1 power track 250 V AC, maximum load current: 32 A
Device presentation	Control element
Standards	IEC 61534-21

Environment

Ambient air temperature for operation	-5…40 °C
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	10.6 cm
Package 1 Length	82.5 cm
Package 1 Weight	1.17 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	18.3 cm
Package 2 Width	23 cm
Package 2 Length	84.5 cm
Package 2 Weight	8 kg
Unit Type of Package 3	P12
Number of Units in Package 3	72
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	108 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**10**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

EU RoHS Directive	**Compliant**
REACh Regulation	**REACh Declaration**
Halogen-free status	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

End of life manual availability	**No need of specific recycling operations**

Image of product / Alternate images

Alternative





