Product datasheet

Specifications



Power track, Easy series, 25A, 250V, 0.6m, surface mount, grey

A3J2PTSM06_GY_GC

Main

Range	Easy Series
Product or component type	Power track
Main colour tint	Grey
Colour tint	Grey
[Ue] rated operational voltage	250 V
[In] rated current	25 A
Network type	AC
Network frequency	50 Hz
Device mounting	Surface

Complementary

Product compatibility	Socket-outlet
fixing mode	By 2 installation fasteners
Length	600 mm
Height	21.4 mm
Width	80 mm
Material	Aluminium
Surface finish	Matt
surface treatment	Anodised
Ambient air temperature for storage	-5…60 °C
Integrated connection type	1 power track 250 V AC, maximum load current: 25 A
Device presentation	Control element
Standards	IEC 61058-1-2 IEC 61534-21

Environment

Ambient air temperature for operation	-5…40 °C
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	5.5 cm
Package 1 Width	10.6 cm
Package 1 Length	62.5 cm
Package 1 Weight	1.06 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	18.3 cm
Package 2 Width	23 cm
Package 2 Length	64.5 cm
Package 2 Weight	7 kg
Unit Type of Package 3	P12
Number of Units in Package 3	120
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	152 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	44
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations

Image of product / Alternate images

Alternative













