Product datasheet

Specifications



USB socket, Easy Series, type A+C, 21W, white

A3J210UAC_WE

Main

Product or component type	USB socket
Colour tint	White
Main colour tint	White
Type of USB power supply	USB type A + C

Complementary

Range	Easy Series
Device mounting	Electrified track
Device presentation	Complete product
Surface finish	Textured
surface treatment	Untreated
Connector type	USB A+C
Power consumption in W	0.15 W
Integrated connection type	1 USB type A 0...12 V DC, maximum load current: 3 A 1 USB type C 0...12 V DC, maximum load current: 3 A
Material	PC (polycarbonate)
Protection type	Overcurrent protection Over temperature protection
Fixing mode	By clipping locks
Height	74 mm
Width	76 mm
Depth	44 mm
Net weight	82 g
IP degree of protection	IP20
Rated current	0.45 A

Environment

Ambient air temperature for operation	-5…40 °C
Ambient air temperature for storage	-5…60 °C
Relative humidity	0…95 %
Standards	IEC 62368-1

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	7.7 cm
Package 1 Length	9.4 cm
Package 1 Weight	100 g
Unit Type of Package 2	S03
Number of Units in Package 2	90
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	9.75 kg
Unit Type of Package 3	P12
Number of Units in Package 3	2160
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	245.9 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	49
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information

Image of product / Alternate images

Alternative






A3J210UAC_WE
IEC 62368-1
L
N
输入 /Input:
220V-250V~50/60Hz Max 0.45A
输出 /Output:
A+C port: 5V⎓3.2A
(单口最大2.4A/Single port max 2.4A)
C port: 5V⎓3A 9V⎓2.33A 12V⎓1.75A
A port: 5V⎓3A 9V⎓2A 12V⎓1.5A
Made in China




OFF
ON
MAX 21W
Schneider
Electric